SHIELDED 2 PAIR 8723 EQUIVALENT

STRANDED TINNED COPPER



Security Cable




Overview

Dynamic Cable Solutions range of security and data cable has been manufactured and compliance tested to meet Australian standards. Our cable is 100% bare copper and features count down meter marking to ensure you know how much cable is left in your box. 1 - 10 individual markings on the sheath to assist with easy cable identification and available on a 100m reel or fitted on a pull reel in a 305m box.

Part Code	Description	
CM87234C1	Dynamic Cable Solutions Shielded 2 Pair 8723 Equivalent, 100m Reel, Grey	
CM87234C1305	Dynamic Cable Solutions Shielded 2 Pair 8723 Equivalent, 305m Box, Grey	





Physical Structure

1.1	Conductor Diameter	7x0.254 ± 0.003mm
1.2	Conductor Material	Stranded Tinned Copper
1.3	Insulation Colour	Red/Black, White/Green
1.4	Insulation OD	1.23 ± 0.05mm
1.5	Insulation Thickness	0.23 ± 0.02mm
1.6	Indivdual Screen	Aluminum/Polyester Laminate Tape
1.7	Drain Wire	7*0.20 ± 0.003mm Stranded Tinned Copper
1.8	Jacket OD	4.80 ± 0.20mm
1.9	Jacket Nom. Thickness	0.60 ± 0.05 mm
1.10	Jacket Material	75°C Flame Retardant PVC
1.11	Jacket Colour	Grey



Test Standards

AS/CA S008:2020

Flame retardancy to AS/NZS IEC 60332.1.

Distributed by LSC

dynamiccable.com.au

Victoria [HQ]

140-158 Dryburgh Street North Melbourne, VIC 3051

p 03 9329 7222 f 03 9329 2570 e vic@lsc.com.au

New South Wales

44 Skarratt Street Silverwater, NSW 2128

p 02 9647 8111 f 02 9647 8100 e nsw@lsc.com.au

Queensland

15-17 Jeays Street Bowen Hills, QLD 4006

p 07 3252 1056 f 07 3252 1087 e qld@lsc.com.au

South Australia 333 Halifax Street

Adelaide, SA 5000 p 08 8223 2999 f 08 8223 1777

e sa@lsc.com.au

Western Australia

9 Brennan Way Perth, WA 6104

p 08 9328 7488 f 08 9227 7363 e wa@lsc.com.au