Agility 4™ | System Architecture

riscogroup.com.au

- Main Panel Supports 32 x WL Devices
- 3 x WL Keypads, 3 x WL Sirens
- 300 Meters LOS range
- RF Coms will Vary depending on the Premises Construction

Plug-In PSTN Modem

RW132MD2400A

Plug-In Multi-Socket IP Module

RP512IP0000A

Plug-In 3G Module

RP512G30000A



2-Way Wireless

Agility 4 Main Panel

RW132V431C0E IP + PSTN

RW132V4D1C0E 3G only

32 WL Zones

3 Partitions

1 x I/O Expander (4 In-puts/4 Outputs)

32 User Codes

500 event Log

8 x PIR Cameras

Voice Built-In

WAN

PC to Panel Cable

RW132EUSB00A

WL Twin Beam

RWT740000H

RISCO Cloud Server

Monitoring Stations

Configuration Software

www.riscocloud.com/installer

www.riscocloud.com

web interface

iRISCO APP

WAN

App Store Play Store iRISCO

VU-Point Cameras + VU-Point NVR

Unlimited Cameras per Site

Only One NVR per Site POE x4, or x 8, non-POE x 16

WL Panda Keypad

RW332KPP400A

916 MHz

433 MHz

WL Smoke & Heat Detector

RWX35S00400C

WL iWave PIR

RWX95P43300B

WL eyeWave PIR Camera

RWX95CMP40C

WL Glassbreak

RWT6G043300C

WL Outdoor Curtain DT

RWX107DT400A

WL Beyond Outdoor DT / DT Camera



RWX350D0400A

RWX350DC400A

2-Way Panda Keyfob

RW332KF1800A

Panic Keyfob

RWT52P43300A

1-Way Keyfob

RP296T4RC00B

8 x Rolling Code Keyfobs per System

Wristband Panic

RWT51P40000A

x 32 Zone/Panic Keyfobs per system

Wireless Outdoor Sounder

RWS401B4000B

WL Indoor Sounder

RWS42043300A

WL Shock and Reed

RWT62W43300B

WL Door/Window Contacts

RWX73F43300A

WL I/O Module

RW132I040AUH