


Garland's Pro Series range is the experts' choice for high quality cables.

LAN Cable


Part No: UTPL6BL

Description	Solid 23AWG (0.57mm) PACW, UTP, 4Pairs, Cross-web Separator, Rip Cord, PE Insulation, PVC Sheath.
Applicable Standards	UL444, ANSI/TIA 568-C.2, ISO/IEC 11801, AS/NZS 3080, AS/CA S-008, AS 1049
Suitable Applications	Used in Structured cabling for computer networks operating up to 1 Gbit on Class E links. Suitable for 10BaseT, 100BaseT and 1000BaseT Ethernet applications.

Cable Construction Drawing



Cable Construction Relative Parts



Cable Description

Conductor	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material
	23	1/0.57	0.255	0.57	PACW
Insulation	Pairs : 4 Material : PE Colour : Blue/White-Blue Stripe, Green/White-Green Stripe, Nominal Thickness (mm) : 0.21 Nominal OD (mm) : 1.0 Colour : Orange/White-Orange, Brown/White-Brown Stripe Nominal Thickness (mm) : 0.22 Nominal OD (mm) : 1.025				

With Garland, you are always well connected.



Industrial / Power / Data / Security / Fibre



Garland's Pro Series range is the experts' choice for high quality cables.

Filler	Material : Cross-web Separator , Rip Cord
Sheath	Material : PVC Colour : Blue(Pantone 3015) Nominal Thickness (mm) : 0.58 Nominal OD (mm) : 6.2

Electrical Properties

Max. Conductor DC Resistance @ 20°C	7.316 Ω /km
Max. DC Conductor resistance unbalanced	5%
Nominal Velocity of Propagation	64%
Characteristic Impedance(1-250MHz)	100 $\pm$ 15 Ω
Nom. Mutual Capacitance @ 1KHz	56 pF/m
Max. Capacitance Unbalance @ 20°C	330 pF/100m
Voltage Test : Core to Core	1.5 kV ac/1min
Voltage Test : Core to Sheath	3.0 kV ac/1min

Frequency (MHz)	Min. RL (dB/ 100m, 20°C)	Max. IL (dB/ 100m, 20°C)	Min. NEXT (dB/ 100m, 20°C)	Min. PSNEXT (dB/ 100m, 20°C)	Min. ELFEXT (dB/ 100m, 20°C)	Min. PS ELFEXT (dB/ 100m, 20°C)	Min. LCL (dB/ 100m, 20°C)	VOP %	Max. PD (ns/ 100m, 20°C)	Max. PDS (ns/ 100m, 20°C)
0.150	-----	-----	86.7	84.7	-----	-----	-----	-----	-----	-----
0.772	-----	1.8	76.0	74.0	70.0	67.0	-----	-----	-----	-----
1.0	20.0	2.03	74.3	72.3	67.8	64.8	40	58.5	570	45
4.0	23.01	3.78	65.27	62.27	55.76	52.76	40	-----	-----	-----
8.0	24.52	5.32	60.75	58.75	49.74	46.74	40	-----	-----	-----
10.0	25.0	5.95	59.3	57.3	47.8	44.8	40	54.5	545	45
16.0	25.0	7.55	56.24	54.24	43.72	40.72	38	-----	-----	-----
20.0	25.0	8.47	54.78	52.78	41.78	38.78	37	-----	-----	-----
25.0	24.32	9.5	53.33	51.33	39.84	36.84	36	-----	-----	-----
31.25	23.64	10.67	51.88	49.88	37.9	34.9	35.1	-----	-----	-----
62.5	21.54	15.38	47.36	45.36	31.88	62.5	32.0	-----	-----	-----

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.madisontech.com.au/garland





garland
cables

Industrial / Power / Data / Security / Fibre

Garland's Pro Series range is the experts' choice for high quality cables.

Frequency (MHz)	Min. RL (dB/ 100m, 20°C)	Max. IL (dB/ 100m, 20°C)	Min. NEXT (dB/ 100m, 20°C)	Min. PSNEXT (dB/ 100m, 20°C)	Min. ELFEXT (dB/ 100m, 20°C)	Min. PS ELFEXT (dB/ 100m, 20°C)	Min. LCL (dB/ 100m, 20°C)	VOP %	Max. PD (ns/ 100m, 20°C)	Max. PDS (ns/ 100m, 20°C)
100	21.11	19.8	44.3	42.3	27.8	24.8	30.0	538	538	45
155	21.0	-----	-----	-----	-----	-----	-----	-----	-----	-----
200	18.0	28.98	39.78	37.78	21.78	18.78	27.0	-----	-----	-----
250	17.32	32.85	38.33	36.33	19.84	16.84	26.0	536	536	45

Mechanical Properties

Operating Temperature Range -15 to 70°C

Max. Recommended Pulling Tension 142N

Min. Bend Radius (install) 62mm

Approximate Mass 4.64kg/100m

Sheath Printing

 GARLAND UTPL6 - 23AWG 4 PAIR - E316183-MT
c(UL)us CMX 75°C - Verified (UL) CAT.6 ANSI/TIA-
568C.2

Supply Information

Pack Size	Pack Type	Dimensions	Qty Per Carton	Cartons Per Pallet
305m	Plastic Reel	W36 x 26.6cm	1R	27

Document Change Record	Issue	Date	Prepared by	Approved By
	01	10-12-2012	LLS	Pent
Change History	Issue	Change		

With Garland, you are always well connected.

Sales Enquiries 1800 66 99 99
www.madisontech.com.au/garland

