



## Material Safety Data Sheet

Issue Date: February 25, 2010

Revised Date: April 15, 2019

Reason: S1 Added Importer details S15 Added Australian Regulation Information

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Super Lube® Dri-Film Aerosol

**Item No:** 11006, 11016

**Product use:** Lubricant

**Importer / Supplier Company address:**

Locksmith Supply Company Pty Ltd  
140-158 Dryburgh Street  
North Melbourne, VIC 3051

**Contact Information:**

Telephone: 03 9329 7222  
Emergency telephone: 03 9329 7222 & Poisons 13 11 26  
Internet: [www.lsc.com.au](http://www.lsc.com.au)

**Emergency Phone Number:** 13 11 26 (Poisons Information Centre)

### 2. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

**Physical state:** Aerosol

**Color:** Translucent

**Odor:** Aliphatic

**WHMIS hazard class:** A, B.5

**HMIS RATING:**

Health: 1

Fire: 4

Physical: 0

**DANGER:**

CONTENTS UNDER PRESSURE  
VAPOR MAY CAUSE FLASH FIRE  
HARMFUL IF INHALED  
CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION



**F+ EXTREMELY FLAMMABLE**

**Relevant routes of exposure:**

Skin, Inhalation, Eyes

**Potential Health Effects**

**Inhalation:**

Vapors and mists will irritate the respiratory tracts and nasal passages. Overexposure may cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

**Skin contact:**

Irritating to skin.

**Eye contact:**

Contact with eyes will cause irritation.

**Ingestion:**

Not expected under normal conditions of use.

**Existing conditions aggravated by exposure:**

None generally recognized.

**See Section 11 for additional toxicological information.**

**Classification of the substance or mixture**

- Hazardous Chemical as listed on HCIS
- Dangerous Goods listed on ADG Code 2017 Table 3.2.3

**GHS Label Elements:**



GHS02 (Flame)



GHS07 (Exclamation Mark)



GHS08 (Health Hazard)



GHS09 (Environment)



GHS02 (Flame)






GHS04 (Gas Cylinder)

Chemical	Code	Health Hazard Statement	Hazard Category	Signal Word
Hexane 110-54-3	H315 (Causes skin irritation) H361f (Suspected of damaging fertility) H336 (May cause drowsiness or dizziness) H373 (May cause damage to organs through prolonged or repeated exposure) H304 (May be fatal if swallowed and enters airways) H225 (Highly flammable liquid and vapour) H411 (Toxic to aquatic life with long-lasting effects)	Skin irritation – category 2 Reproductive toxicity – category 2 Specific target organ toxicity (single exposure) – category 3 Specific target organ toxicity (repeated exposure) – category 2 Aspiration hazard – category 1 Flammable liquid – category 2 Hazardous to the aquatic environment (chronic) – category 2	Warning	
Butane 106-97-8	H220 (Extremely flammable gas)	Flammable gas – category 1 Gasses under pressure	Danger	
Polytetrafluoroethylene 9002-84-0				
Carbon Dioxide 124-38-9				

<b>Precautionary Statements - Prevention</b>	
P264	Wash ... thoroughly after handling
P280	Wear protective gloves
P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P281	Use personal protective equipment as required
P261	Avoid breathing dust/fume/gas/mist/ vapours/spray
P271	Use only outdoors or in a well-ventilated area
P260	Do not breathe dust/fume/gas/mist/ vapours/spray
P210	Keep away from heat/sparks/open flames/hot surfaces.– No smoking
P233	Keep container tightly closed
P240	Ground/Bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/ lighting/.../equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P280	Wear protective gloves/eye protection/face protection
P273	Avoid release to the environment
<b>Precautionary Statements - Response</b>	
P302 + P352	IF ON SKIN: Wash with plenty of soap and water
P321	Specific treatment (see ... on this label) ... Reference to supplemental first aid instruction
P332 + P313	If skin irritation occurs: Get medical advice/attention
P362	Take off contaminated clothing and wash before reuse
P308 + P313	IF exposed or concerned: Get medical advice/attention
P304 + P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P331	Do NOT induce vomiting
P303 + P361 + P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P370 + P378	In case of fire: Use ... for extinction
P391	Collect spillage.
<b>Precautionary Statements – Storage</b>	
P405	Store locked up
P403 + P235	Store in a well-ventilated place. Keep container tightly closed
P405	Store locked up.
<b>Precautionary Statements – Disposal</b>	
P501	Dispose of contents/container to... in accordance with local/regional/national/international regulations

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous Components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Hexane 110-54-3	27-32	50 ppm TLV	176 mg/m <sup>3</sup> TWA	None
 Xn, F, N;R11-38-48/20-62-65-67-51/53				
Propane 74-98-6	27-32	1000 ppm TWA	1800mg/ m <sup>3</sup>	None
 F+; R12				
Butane 106-97-8	27-32	1000 ppm TWA	2400mg/ m <sup>3</sup>	None
 F+; R12				

Additional information: For the wording of the listed risk phrases refer to section 16.

#### Other components

Polytetrafluoroethylene 9002-84-0	3-5	Not established	Not established	None
Carbon Dioxide 124-38-9	1-3	5000 ppm TWA	9100mg/ m <sup>3</sup>	None
Proprietary Additives	1-2	Not established	Not established	None

### 4. FIRST AID MEASURES

<b>Inhalation:</b>	Remove to fresh air. Restore breathing.
<b>Skin contact:</b>	After contact with skin, wash immediately with plenty of water. Immediately flush skin with plenty of water (using soap, if available). Get medical attention if symptoms develop and persist.
<b>Eye contact:</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
<b>Ingestion:</b>	Do not induce vomiting. Get medical attention immediately.
<b>Notes to physician:</b>	Treatment:

## 5. FIRE-FIGHTING MEASURES

<b>Flash point:</b>	Not available
<b>Autoignition temperature:</b>	Not available
<b>Flammable/Explosive limits-lower %:</b>	1.1 (vol %)
<b>Flammable/Explosive limits-upper %:</b>	9.5 (vol %)
<b>Extinguishing media:</b>	Carbon dioxide (CO <sub>2</sub> ). Dry chemical. Foam.
<b>Special fire fighting procedures:</b>	Water spray may be ineffective. Water should be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.
<b>Unusual fire or explosion hazards:</b>	Closed containers may rupture (due to build up of pressure) when exposed to temperatures exceeding 120°F (48.9°C).
<b>Hazardous combustion products:</b>	Oxides of carbon.
<b>Sensitivity to mechanical impact:</b>	Not available
<b>Sensitivity to static discharge:</b>	Not available

## 6. ACCIDENTAL RELEASE MEASURES

<b>Environmental precautions:</b>	No information available
<b>Clean-up methods:</b>	Remove all ignition sources. Ventilate area. Soak up with inert absorbent.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. Do not breathe mist or vapors.
<b>Storage:</b>	Do not puncture, incinerate, or expose to temperatures above 48.9° C (120° F). Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause containers to burst.
<b>Incompatible products:</b>	None reasonably foreseeable.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Engineering controls:</b>	Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.
<b>Respiratory protection:</b>	If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH.
<b>Skin protection:</b>	Chemical resistant, impermeable gloves.
<b>Eye/face protection:</b>	Safety glasses with side-shields.

See Section 3 for exposure limits.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Aerosol
<b>Color:</b>	Translucent
<b>Odor:</b>	Aliphatic
<b>Odor Threshold:</b>	Not available
<b>Vapor pressure:</b>	5.0 – 5.5 BAR @ 20° C
<b>pH:</b>	Not applicable
<b>Boiling point/range:</b>	Not available
<b>Melting point/range:</b>	Not available
<b>Specific gravity:</b>	Not available
<b>Vapor density:</b>	Heavier than air
<b>Evaporation rate:</b>	Faster than ether
<b>Solubility in water:</b>	Not soluble
<b>Partition coefficient (n-octano/water):</b>	Not available
<b>VOC content:</b>	99.2%

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable
<b>Hazardous polymerization:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	None under normal use.
<b>Incompatibility:</b>	None known.
<b>Conditions to avoid:</b>	Heat, flames and sparks.

## 11. TOXICOLOGICAL INFORMATION

**Product toxicity data:** Not available

**Toxicologically synergistic products:** Not available

**Refer to the following for irritancy of Product, Sensitization to Product, Carcinogenicity, Reproductive Toxicity, Teratogenicity, and Mutagenicity.**

### Ingredient Toxicity Data & Carcinogen Status

Hazardous components	LD50s & LC50s	Other LD50s and LC50s	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen	ACGIH-Carcinogen
Hexane 110-54-3	Inhalation LC50 (Rat) = 620 g/m <sup>3</sup>	Oral Rat, LD50,25gm/kg	No	No	No	No
Propane 74-98-6	Inhalation LC50 (Rat) = 800000 ppm/15 min.		No	No	No	No
Butane 109-97-8	Inhalation LC50 (Rat) = 658 g/m <sup>3</sup> /4hrs		No	No	No	No
<b>Other components</b>						
Polytetra- fluoroethylene 9002-84-0	Not determined	None	No	No	No	No
Carbon Dioxide 124-38-9	Inhalation LC50 Human = 100000 ppm/min.	None	No	No	No	No
Proprietary Additives	Not determined	None	No	No	No	No

### Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Hexane 110-54-3	Central nervous system, respiratory system, eyes, skin, peripheral nervous system, testes.
Propane 74-98-6	Central nervous system
Butane 109-97-8	Central nervous system
<b>Other components</b>	
Polytetrafluoroethylene 9002-84-0	Irritant
Carbon Dioxide 124-38-9	Harmful by inhalation
Proprietary Additives	Not determined

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available

## 13. DISPOSAL CONSIDERATIONS

**Information provided is for unused product only.**

**Recommended method of disposal:** Dispose of in accordance with federal and local regulations.

## 14. TRANSPORT INFORMATION

### **Transportation of Dangerous Goods – Ground:**

**Proper shipping name:** Consumer Commodity, ORM-D  
**Hazardous class or division:** None  
**Identification number:** None  
**Packing group:** None

### **International Air Transportation (ICAO/IATA):**

**Proper shipping name:** Aerosols, Flammable  
**Hazardous class or division:** 2.1  
**Identification number:** UN 1950  
**Packing group:** Y203  
**Exceptions:** (Not more than 500 ml) May qualify as Consumer Commodity ID8000

### **Water Transportation (IMO/IMDG):**

**Proper shipping name:** Aerosols, LTD. QTY.  
**Hazardous class or division:** 2  
**Identification number:** UN 1950  
**Packing group:** None  
**Marine pollutant:** None



## 15. REGULATORY INFORMATION

15.1 Safety, health and environment regulations/legislation specific for the substance or mixture

Regulatory	Chemical	Status
Australian Inventory of chemical substances (AICS) (NICNAS)	Hexane 110-54-3 Butane 106-97-8 Polytetrafluoroethylene 9002-84-0 Carbon Dioxide 124-38-9	Listed Listed Listed Listed
Australian Hazardous Substances Information System List (HCIS)	Hexane 110-54-3 Butane 106-97-8	Listed Listed
Australian Exposure Standards (HCIS, SWA)	Hexane 110-54-3 Butane 106-97-8 Carbon Dioxide 124-38-9	Listed Listed Listed
International Agency for Research on Cancer (IARC) Monographs	Polytetrafluoroethylene 9002-84-0	Listed
Poisons Schedule		

**Code letter and hazard designation of product:**

F+ Extremely flammable.

**Risk phrases:**

12 Extremely flammable.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapors may cause drowsiness and dizziness.

**Safety phrases:**

3/7 Keep container tightly closed in a cool place.

16 Keep away from sources of ignition-No smoking.

23 Do not breathe fumes/aerosol.

51 Use only in well ventilated areas.

**Special labeling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn even after use.

Keep out of reach of children.

**National regulations:**

**Water hazard class:**

Water hazard class 1 (Self-assessment): slightly hazardous for water.

### **Canada Regulatory Information**

**CEPA DSL/NDSL Status:** All components are listed on or are exempt from listing on the Domestic Substances List.

### **United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

## **SECTION 16: OTHER INFORMATION**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Product Regulations.

### **Relevant R-phrases:**

12 Extremely flammable

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapors may cause drowsiness and dizziness.

Data prepared by Environment protection department.