







SureClose® 108 Flush Mount (screw-on)














SureClose® 57 Centre Mount (screw-on)













Plan view - Centre Mount



Plan view - Flush Mount



D&D Technologies

AUSTRALIA: D&D Technologies P/L, Unit 6, 4-6 Aquatic Drive,

New Zealand Regional Sales Manager. Mobile: 027 5482 714

E-mail: iellis@ddtech.com.au Web: www.ddtechglobal.com

Fax: (02) 9454 7600. E-mail: sales@ddtech.com.au

NEW ZEALAND: D&D Technologies P/L

Frenchs Forest NSW 2086 Tel: 1800 500 203 or (02) 9454 7800

www.ddtechglobal.com/sureclose

Available from:

COMMERCIAL GRADE

Hydraulic Gate Closers & Hinges



For steel & aluminium gates

www.ddtechglobal.com/sureclose

Precision engineered and superbly finished...

SureClose® devices are either a Hinge or a Hinge Closer, in one small, powerful package!

Mounting Brackets: A variety of gate brackets allow for

virtually all square-post application:

• Aluminium Screw-On

• Steel Weld-On



Thrust bearings:

high load. Tested to

over 680kg.

Superbly engineered for

Powerful, hidden hydraulics that don't leak!:

Multiple adjustment

• Final snap-close action

Variable Speed

Hydraulics are concealed within the post, providing a controlled close and a tamper-resistant, compact design

Ideal solution for:

- Commercial/Industrial gates
- High-end residential gates
- Security gates
- Government institutions
- Airports
- Units & Apartments

Suitable for child/pool safety gates

- Childcare Centres
- Access Control gates
- Schools & Playgrounds
- Theme parks
- Hotel/Motel properties
- Sporting arenas

Centre Mount Brackets:

Gate swings 900 IN and OUT

NON-SF models have built-in

hold-open at 90°, so they

are NOT SUITABLE for

child/pool safety gates


SF models for child/pool

safety only open to 90⁰.

NO built-in hold at 90°.

DO NOT PROP GATE OPEN.

Understanding Gate Sweep variations...



Gate Hinges & Closers

commercial gate hinges and sturdy hinges provide greater commercial industrial hinges. design conceal the hydraulics quality with SureClose® gate closers and hinges.

Centre Mount

Centre of gate and

post are aligned

Model 108 & 108SF

Final snap-close action

increases speed at

the end to ensure

latch engagement.

Models 57 & 108

self-close from 900 to 00

SureClose® Gate Closers and Hinges are designed to replace conventional closers. These strong and strength than traditional In some models the superb engineering and patented within the fence post. There is no compromise of

Screw-on Post Brackets

Centre Mount

SureClose SM S

NON-SELF-CLOSING

Flush Mount

SureClose SM AT90 S

NON-SELF-CLOSING

. Gate sweep: 90° in and out



SURECIOSE SCREW-ON - Aluminium & Steel Gates

SureClose 57SF S

SELF-CLOSING FROM 90°

• Gate sweep: 90° in and out

(suitable for pool/safety gates

SureClose 57SF AT90 S

(suitable for pool/safety gates)

SELE-CLOSING FROM 90°

Gate sweep: 90° one way

No hold-open feature

No hold-open feature





SureClose 108 S

SELF-CLOSING FROM 85°

•Gate sweep: 90° in and out

Holds gate open at 90°

Adjustment tool included

SFI F-CLOSING FROM 85°

. With final snap-close action

Holds gate open at 90°-180°

· Adjustment tool included

Code: 75108113m





SureClose 108 AT90 S SureClose 108SF AT90 S



SureClose 108SF S

SELF-CLOSING FROM 90°

· Adjustment tool included

ates) • No hold-open feature

With final snap-close action

• Gate sweep: 90° in and out

SELE-CLOSING FROM 90°

No hold-open feature

. With final snap-close action

(suitable for pool/safety gates)

Closer/Hinge + Aluminium Screw-on Gate Bracket^{*}

SureClose 57 S

• Holds gate open at 90°

SELF-CLOSING FROM 85°

• Gate sweep: 90° in and out

SureClose 57 AT90 S

SELE-CLOSING FROM 85°

· Gate sweep: 180° one way

• Holds gate open at 90°-180°

(not suitable for pool/safety ga

		Max. Weigh	nt		Maximum	Snap-Close	**Pool/Child	Horizontal		Fence Post
Model	Description	Self Close	Prod. Code	Self Closes	Gate Swing	Action	Safety	Adjustment	Hinge Gap	Size
CENTR	E MOUNT									
SM S	Hinge: Plain, pivoting	-	75001113	-	90°, in AND out	-	-	Yes	63-76mm	50mm+
57 S	Closer Hinge: General purpose	40kg	75057113m	Yes, from 85°	90°, in AND out	-	-	Yes	63-76mm	50mm+
57SF S	Closer Hinge: Ideal for safety gates	40kg	75057123m	Yes, from 90°	90°, in AND out	-	Yes	Yes	63-76mm	50mm+
108 S	Closer Hinge: Final snap-close action	80kg	75108113m	Yes, from 85°	90°, in AND out	Yes	-	Yes	63-76mm	75mm+
108SF S	Closer Hinge: Safety, with snap-close	80kg	75108123m	Yes, from 90°	90°, in AND out	Yes	Yes	Yes	63-76mm	75mm+
FLUSH	MOUNT									
SM AT90 S	Hinge: Plain, pivoting	-	75001213	-	180° one way	-	-	-	13mm	50mm+
57 AT90 S	Closer Hinge: General purpose	40kg	75057213m	Yes, from 85°	180° one way	-	-	-	13mm	50mm+
57SF AT90 S	Closer Hinge: Ideal for safety gates	40kg	75057223m	Yes, from 90°	90° one way	-	Yes	-	13mm	50mm+
108 AT90 S	Closer Hinge: Final snap-close action	80kg	75108213m	Yes, from 85°	180° one way	Yes	-	-	13mm	75mm+
108SF AT90 S	Closer Hinge: Safety, with snap-close	80kg	75108223m	Yes, from 90°	90° one way	Yes	Yes	-	13mm	75mm+

Post Mounting Brackets sold separately*

		9			
Prod. Code	Mounting Style	Description	Suggested Fasteners	Horizontal Adjustment	Fence Post Size
7511	Centre Mount	Aluminium Screw-on	#18 c.s.	Yes, threaded	50mm+
7512	Centre Mount	Aluminium Screw-on	#14 c.s.	Yes, threaded	50mm+
7513	Centre Mount	Aluminium Screw-on	#14 c.s.	Yes, threaded	75mm+
7514	Centre Mount	Aluminium Screw-on (single)***	#14 c.s.	Yes, rotate hinge	50mm+
7515	Flush Mount	Aluminium Screw-on	#18 c.s.	No	50mm+

HANDY HINT: Mix & Match Closers/Hinges It is possible to mix and match SureClose hinges and closers. For example, it is possible to combine a plain, pivoting SM model with either a 57 or a 108 self-closing model to attain self closure. The following table shows how hinge models can be paired to obtain different types of gate closure (based on max gate size 1800H x 1000mmW):

	Max. Self-Closing
<u>Models</u>	Gate Weight
57 + SM	40kg
57 + 57	80kg
108 + SM	80kg
108 + 108 (welded only)	120kg
SM + SM (no self-close)	680kg (point load



SURECIOSE® WELD-ON - Steel Gates

Centre Mount



SureClose SM W NON-SELF-CLOSING


Flush Mount

SureClose SM AT90 W

NON-SELF-CLOSING







SELE-CLOSING FROM 85°


· Gate sweep: 180° one way

• Holds gate open at 90°-180°

(not suitable for pool/safety gates)



SureClose 57SF W SureClose 57 W SELF-CLOSING FROM 85° SELF-CLOSING FROM 90






•Gate sweep: 90° in and out Holds gate open at 90°



SureClose 108 W Code: 75108114m SELF-CLOSING FROM 85°

· Adjustment tool included

SELF-CLOSING FROM 90° . With final snap-close action . With final snap-close action • Gate sweep: 90° in and out (not suitable for pool/safety gates) • No hold-open feature



SureClose 108SF W



SureClose 108 AT90 W

SureClose 108SF AT90 W SELF-CLOSING FROM 85° . With final snap-close action SELE-CLOSING FROM 90°

· With final snap-close action Holds gate open at 90°-180° • Gate sweep: 90° one way

• No hold-open feature Adjustment tool included · Adjustment tool included

Weld-on Post Brackets



SureClose 57 AT90 W SureClose 57SF AT90 W

SELF-CLOSING FROM 90°

· Gate sweep: 90° one way

Adjustment tool included

(suitable for pool/safety gates)

No hold-open feature

Closer/Hinge + Steel Weld-on Gate Bracket*

	, and the second se	Max. Weight			Maximum	Snap-Close	**Pool/Child	Horizontal		Fence Post
Model	Description	Self Close	Prod. Code	Self Closes	Gate Swing	Action	Safety	Adjustment	Hinge Gap	Size
CENTR	RE MOUNT									
SM W	Hinge: Plain, pivoting	-	75001114	-	90°, in AND out	-	-	Yes	63-76mm	50mm+
57 W	Closer Hinge: General purpose	40kg	75057114m	Yes, from 85°	90°, in AND out	-	-	Yes	63-76mm	50mm+
57SF W	Closer Hinge: Ideal for safety gates	40kg	75057124m	Yes, from 90°	90°, in AND out	-	Yes	Yes	63-76mm	50mm+
108 W	Closer Hinge: Final snap-close action	80kg	5108114m	Yes, from 85°	90°, in AND out	Yes	-	Yes	63-76mm	75mm+
108SF W	Closer Hinge: Safety, with snap-close	80kg	75108124m	Yes, from 90°	90°, in AND out	Yes	Yes	Yes	63-76mm	75mm+
FLUSH	MOUNT									
SM AT90 W	Hinge: Plain, pivoting	-	75001214	-	180° one way	-	-	-	13mm	50mm+
57 AT90 W	Closer Hinge: General purpose	40kg	75057214m	Yes, from 85°	180° one way	-	-	-	13mm	50mm+
57SF AT90 W	Closer Hinge: Ideal for safety gates	40kg	75057224m	Yes, from 90°	90° one way	-	Yes	-	13mm	50mm+
108 AT90 W	Closer Hinge: Final snap-close action	80kg	75108214m	Yes, from 85°	180° one way	Yes	-	-	13mm	75mm+
108SF AT90 W	Closer Hinge: Safety, with snap-close	80kg	75108224m	Yes, from 90°	90° one way	Yes	Yes	-	13mm	75mm+

Post Mounting Brackets sold separately*

Prod. Code	Mounting Style	Description	Horizontal Adjustment	Fence Post Size
7525	Flush Mount	Steel Weld-on	Yes, threaded	50mm+
7526	Centre Mount	Steel Weld-on	Yes, threaded	50mm+

NOTE: Screw-on aluminium brackets may be powdercoated or painted. Protect threads and moving parts when applying finish

* All closers/hinges come with a gate-mounting bracket included, but post-mounting brackets are sold separately. ** Yes = Gates will not hold open at 90°, so therefore are suitable for safety gates. Do NOT use a hinge with 90° hold-open feature on pool/child safety gate



pool safety gates.



HANDY HINT: Safety Gate Closer Hinges

Brass end-caps indicate a self-closing hinge,

but not all self-closing models are suitable for

safety gates. A 5th dimple (see below) on some

end-caps signifies an "SF" model, or Safety Gate

model, meaning it IS suitable for use on child and

NOTE: Screw-on aluminium brackets may be powdercoated or painted. Protect threads and moving parts when applying finish.

* All closers/hinges come with a gate-mounting bracket included, but post-mounting brackets are sold separately.

** Yes = Gates will not hold open at 90°, so therefore are suitable for safety gates. Do NOT use a hinge with 90° hold-open feature on pool/child safety gates.

*** Post mounting bracket 7514 allows for single-hinge applications such as turnstiles. Includes fixing clamp to prevent slippage. For additional products, detailed instructions and specifications, visit www.ddtechglobal.com/sureclose