

# 13.5Vdc 3.5A ECO Series

MODELS :

TPS13-3.5DC



SECURITY POWER SUPPLIES

© 2022 The contents of this manual are copyright and may not be reproduced without the written permission of Tactical Power Products Pty Ltd.



## Installation Manual



# 13.5Vdc



# 3.5A Specifications

## Specifications :

( In the interests of product improvement, Tactical reserves the right to change specifications without notice)

Eco Range®	3.5DC	3.5DC & Small Kit	3.5DC S/Kit & PDM	3.5DC & Med Kit	3.5DC & M/Kit& PDM
Output Voltage	13.5 Vdc				
Output Current	3.5A Continuous				
Output Channels	1	1	10	1	10
Output per Channel	3.5A	3.5A	350mA	3.5A	350mA
Input Voltage	240 V ac ( +6% / -10% ) 50Hz				
Input Current	1A @ full load				
Input In-Rush Current	<20A ( 25 <sup>0</sup> C cold start up )				
Battery Charger	13.5Vdc / 300mA (Max)				
Low Battery Indicator	1 x SPDT relay & Red LED				
AC Input Indicator	1 x SPDT Relay & Green LED				
Weight (Approx)	1Kg	4Kg		6Kg	
Dimensions (mm)	226L x 123W x 60H	250 w x 310 H x 100 D		340 W x 430 H x 145 D	
Overload Protection	Hysteretic thermal shutdown with automatic fault recovery				
Load Regulation	< 1% from open to full load				
Line Regulation	< 0.2%				
Output Ripple	<125mV p-p @ full load (Typical)				
Working Temperature	0 - 40 <sup>0</sup> C without derating				
Revision	B				
Safety Standards	Safety Standard AS NZS 60950:1.2015    Certificate of Approval    SAA 203368-EA				
EMC Standards	AS/NZS CISPR 32:2015 ( Class B Conducted and Radiated )				



[www.tacpower.com.au](http://www.tacpower.com.au)

Securing Your Power Needs®  
Now and into the Future...



Tel: 1300-822-769 | U23/9-12 Lambridge Pl. Penrith NSW 2750 | [sales@tacpower.com.au](mailto:sales@tacpower.com.au)